E EMIS		

Inspector:	Smel	(KC)				
Date of Inspection:	And	1.14				
Shift: 1st Shift or 2nd Shift	Tir	me: 500	(1	
Unit	Visual Inspection NORMAL or ABNORMAL			Com	ments	
Visible Emission From Shaker	nor	on the same of the	ý			
Visible Emission From ■ischarge Conveyor System	nor	V			ħ.	

- Visible inspection must be performed during normal daylight eperations and during the part of eperations that would normally be expected to cause the greatest errissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•	
Inspector: Smello					
Date of Inspection: Apr 2	. 19			,	
Shift: (1 st Shift) or 12 ^{no} Sh	ift Ti	ime: 5:00		,	• • .
Unit	Visual Inspection NORMAL LOT ABNORMAL		Comp	nents	
Visible Emission From Shaker	noR				
Visible Emission From Discharge Conveyor System	nor	-			

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.

• Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•		•
Inspector: Smelko)	,				
Date of Inspection: A	3 14					
Shift: 1st Shift or 2sts Sh	fift Ti	me: 5:00		; [†]		e e
Unit	Visual Inspection NONMAL For ABNORMAL			omments		
Visible Emission From Shaker	nor	· · ·				
Visible Emission From Discharge Conveyor System	nor				ŗ.	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest errissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS			•	
inspector:				₹' -
Darran Cugjoc	·			•
Date of Inspection:		:		
Shift: 1st Shift or 2st Shift	Time:	,	3	
Sint. F Sint of 2 Sint	6.30		. ,	
Unit Visual Inspection N●RMAL		Comme	ıts	
ABNORM/				
Visible Emission From Shaker No. (,		ı
Visible Emission From		δ		
Discharge Conveyor System No			v	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
- pacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

1. 10, 14, Lad 1; hand		NOTATIONS
1 11 12 12 12		WIT V. 1 M. 1 IC 3 M L V.
	(T) () () () () () () () () (171 F 7 1 1 F 7 1 1 1 7 1 7 1 7 1 7 1 7

Inspector: S	melko			•	
Date of Inspection:	<u> </u>				
Shift: 1 st Shift or 2 ^{sto} Sh	ift Th	ime: 500	· ·	1	
Unit	Visual Ins∎ection NORMAL .or A∎N●RMAL			Comments	
Visible Emission From Shaker	nor		~		
Visible Emission From Discharge Conveyor System	nop	· ·		t.))))

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected ause the greatest emissions.

Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS	
Inspector:	
Date of Inspection:	
Shift: 151 Shift or 250 Shift Time: 500 Am	
Unit Visual Inspection NORMAL or ABNORMAL	Comments
Visible Emission From Shaker No/	
Visible Emission From Discharge Conveyor System No	t.

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		·		
Inspector:	Constor				
Date of Inspection:	1141			1	
Shift: 1 st Shift or (2 nd)Sh		me: 5:00 AM			•
Unit	Visual Inspection NORMAL or ABNORMAL		Comment	S	
Visible Emission From Shaker	Nel				
Visible Emissien From Discharge ConVeyor System	Nor		-		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

ANOTHER PRINTAGENIA IAC IV	1 11/0/11 0		
Inspector: Smelku	·		
Date of Inspection: Apr	7,314		••••••••••••••••••••••••••••••••••••••
Shift: 15 Shift or 2 ^{m2} Sh		me:	
Unit	Visual Inspection NORMAL or ABNORMAL		Comments
Visible Emission From Shaker	nor		ir ir
Visible Emission From Discharge Conveyor System	nor	**mulgaggase**	t.

• Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.

• Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS				
Inspector: Smelko				#1
Date of Inspection: Acc \$ 14				3 5 -
Shift: 1 st Shift or 2 ^{std} Shift Time	520			
Unit Visual Inspection NORMAL ABNORMAL		Comments		
Visible Emission From Shaker 1000				:
Visible Emission From Discharge Conveyor System NOR	J		ъ.	:

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		•	in the second
Inspector: Smella				
Date of Inspection:				
Shift: (1st Shift) or 2nd Sh	ift Ti	me: 500	 1	
Unit	Visual Inspection NORIMAL Or ABNORMAL		omments	
Visible Emission From Shaker	NOR	garlaner+.		
Visible Emission From Discharge Conveyor System	NOO :	E _{lider} er		1

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS				•		
Inspector: Society			1				
Date of Inspection: A	161						,
Shift: 1st Shift or 2nd Sh	}	me: 51.00	•		,		**
Unit	Visual Inspection NORMAL OF ABNORMAL			Co	mments		
Visible Emission From Shaker	NOR	estation ,	a	"			
Visible Emission From Discharge Conveyor System	nor	1				e .	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected a cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	MONS ·			•		
Inspector: Davren	7) Cudjoe	~				
Date of Inspection: 4-1	2-204		:			z 4
Shift: 1" Shift or Shi	ft: Ti	me: 5/30		ì		· *
Unit	Visual Inspection NORMAL Lot ABNORMAL			Comment	\$	
Visible Emission From Shaker Visible Emission From	Nor		ş			
Discharge Conveyor System	Nor				k .	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected ause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS					\cdot
Inspector: Smelko	,					
Date of Inspection:	13 14					
Shift: 2 Shift or 2 Sh		nie: 5.00	,			
Unit	Visual Inspection NORMAL For ABNORMAL			C⊕mment		
Visible Emission From Shaker	NOR	ustilishing.	ý			<u>;</u>
Visible Emission From Discharge Conveyor System	NOR				£	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		•	
Inspector:	ne (KO			
Bate of Inspection:	, - 14,14		1	•
Shift: 1 Shift or 2 Sh	ift Ti	me: 5100		. ,
Unit	Visual Inspection NORMAL Or ABNORMAL		omments	
Visible Emission From Shaker	nos	waterproject		
Visible Emission From Discharge Conveyor System	no2 .	Metgyus.,		

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest errissions.

• Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

THENTHE	THE REPORT OF THE REAL PRINCES	BI CYCK TI	M 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
V1 30 15 15 15	EMISSION	19113114111	1141.7

, we consider the control of the con			••••		•
Inspector:	Smelle				
Date of Inspection:	W is id				ť
January Commence of the Commen	TO CLOUD			3	·
Shift: 1shift or 2sh Sh	ift Ti	me: 51,00		,	• •
Unit	Visual Inspection NORMAL OF ABNORMAL			omments	
Visi⊌le Emission From Shaker	NOR	- 440 ₀₀₀₄			
Visible Emission From Discharge Conveyor System	nor.	linguist*		t	

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
 Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the

background.

The colon is the		NOTATIONS
V 21 % (() ()	1-1711 1 mg miles 111 1111	No. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

Inspector:	
Impactor Smallo	
Date of Inspection:	
Date of mopection.	
Shift: 1 Shift or 2 Shift Time:	, ,
Shift: (Shift or 2 ^{no} Shift Time:	5
with the Unit of the Property Misual	Comments with the control of the Comments of the control of the co
Inspection	선물에 그는 전쟁은 선명할 하신 수 범인 교육에 사기 본산 내 하다 못했다. 남극 양년 이상환 현업을 받았다. 현업으로 되었다.
NORMAL	[[성] 보는 문제를 가는 그리라면 이번 회에 하면 [[기 시간되다. 그리죠[[성] 기고 이 방 논리를 확할 함으를 모양한다.
Carlos Constitution of the	골네. 이 문학 강한 일하는 일본 하시하면 하면 가는 물만 하지만 하는 문학들은 전한 기계 가장하셨다고 한 학자 회장을 열었다.
ABNORMAL	가는 보고 있었다. 하는 사람이 모든 모든 모든 사람들이 그리고 있다면 여름이 못 하는 것을 만드셨다.
Visible Emission From Shaker 102	
Visible Emission From	
Discharge Conveyor System VA	
- American	· ·

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected a cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•		•
Inspector:			**************************************		•	36
OMEIRO						
Date of Inspection:	161					*
Shift: (151 Shift or 2110 Sh	to. Ti			, 1		
Shift: 1" Shift or 2" Sh		me: 500		,		
Unit	Visual Inspection NORMAL or ABNORMAL			Comments		
Visible Emission From Shaker	noc					
	1 North		<i>i</i>			
Visible Emission From						
Discharge Conveyor System	noe			t		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

יים וו ביינו ביי פני ד		A S. And And Address of the St. J. Aug.
	1 1 1 1 SE SELT 3/81	NOTATIONS
UT CHUSE E	[[[]]]] A Mark [] [] A	181 4 7 1 7 1 1 4 7 1 3 4 7

Inspector: Smello		2			**************************************
Date of Inspection:	3 14				,
Shift: 1st Shift or 2 90 Sh	ift Ti	ime: 500		1	
Unit	Visual Inspection NORMAL OF ABNORMAL		Co mme	ents	
Visible Emission From Shaker	NOR	Indication .			
Visible Emission From Discharge Conveyor System	NOG.			t.	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•	
Inspector:	wer Cans co	<u> </u>	,		
Date of Inspection:	419-2014		,	,	
Shift: 15 Shift or 20 Sh	ift Ti	ime: 5730			
Unit	Visual Inspection NORIMAL LOT ABNORMAL		Comm	ientS	
Visible Emission From Shaker	Nor				
Visible Einissian From ■ischarge Conveyor System	Nor			k.	

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.

 Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		,	
Inspector:	Snelvo			
Date of Inspection:	April 201	4	ı	•
Shift: (1) Shift or 2 ^{frd} Sh	ift Ti	me: 500		• • .
Unit	Visual Inspection NORMAL LOT ABNORMAL		-omments	
Visible Emission From Shaker	NOR	- And Antique		
Visible Emission From Discharge Conveyor System	nor	, ggggilliste.	e	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected acause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TONS		•		
Inspector: Smelko		~			#
Date of Inspection: Apr 21	. 19		1		3
Shift: 1st Shift or 2nd Sh	ift Ti	me: SOO	· · · · · · · · · · · · · · · · · · ·		• •
Unit	Visual Inspection NORMAL OT ABNORMAL		Comments		
Visible Emission From Shaker	nor	especialization .			
Visible Emission From Discharge Conveyor System	nor.	proposad		t.	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOT	ATIONS			•	
Inspector: Darrer	and roll				
Date of Inspection:	22-2014				,
Shift: 1st Shift or 2st S	riff) Ti	ime: 5.30			
Unit	Visual Inspection NORMAL Lor ABNORMAL		Comme	ents	
Visible Emission From Shaker Visible Emission From Discharge Conveyor System	No C			*	

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.

 Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•		
Inspector: Smelko		-				?* • •
Date of Inspection: Apr 23	, 14			3		,
Shift: (15 Shift) or 2 3 Sh	iff: Th	me: 5,00	·	· · · · · · · · · · · · · · · · · · ·	,	
Unit	Visual Inspection NORIMAL Lor ABNORIMAL			Comments		
Visible Enission From Shaker	nor		,			
Visible Emission From Discharge Conveyor System	nor				r.	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected ause the greatest errissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		•		
Inspector: Sm-el/C	> .				
Date of Inspection:	24, 19				
Shift: 1 Shift or 2nd Sh	ift Ti	ime 500	i .		
Unit	Visual Inspection NORMAL For ABNORMAL		Comments		
Visible Emission From Shaker	nor	<u> </u>	 		
Visible Emission From Discharge Conveyor System	non	۵.		.	· · · · · · · · · · · · · · · · · · ·

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.

Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS				,	
Inspector: Smelko		-				*
Date of Inspection:	5 14		1 -			;
Shift 1st Shift or 2 2 Sh	ift O Ti	me: JOO	ĺ		·	· ·
Unit	Visual Inspection NORMAL For ABNORMAL			Commen	rts	
Visible Emission From Shaker	nor		v	"		
Visible Emission From Discharge Conveyor System	noR	/			t.	

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.

 Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS				•	
Inspector:	1. inter					
Pate of Irispection: 4/26/	140				ī	
Shift: 1 st Shift or 2 st Sh	ift Ti	me: SAN	7			
Unit	Visual Inspection NORMAL or ABNORMAL			Comme	nts	
Visible Emission From Shaker	Nor	re-folkeren frankligen frankligen frankligen frankligen frankligen frankligen frankligen frankligen frankligen	and the same of th			
Visible Emission From Discharge Conveyor System	Nor	g new mendmentalisk statute else Capital per vincianisk statute else Capital per vincianisk statute else Capital	DOMESTIC STATE OF THE STATE OF		т.	

Visible inspection must be perfermed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.

 Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			•	,
Inspector: TelC	moiten	4			#* *
Date of Inspection: 4/27/	194			,	* * * * * * * * * * * * * * * * * * *
Shift: 1 st Shift or (2 nd)Sh	ift Ti	me: 5.Am	,		* *
Unit	Visual Inspection NORMAL LOT ABNORMAL			omments	
Visible Emission From Shaker	Nor				
Visible Emission From Discharge Conveyor System	Nov		inno.	į k	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected acuse the greatest errissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS				•		
Inspector: Smelko			:	,			
Date of Inspection: Apr 27	19				}		1
Shift: 1 ⁵¹ Shift or 2 ⁵¹⁰ Sh	ift Ti	me: 5.00					• • .
Unit	Visual Inspection NORMAL Lor ABNORMAL				omments		
Visible Emission From Shaker	noR	Υ .	٠	11			
Visible Errission From Discharge Conveyor System	nor.					ъ.	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS				•	•
Inspector:	· didie	~				· · · · · · · · · · · · · · · · · · ·
Date of Inspection:	4-28-3	2014			,	
Shift: 1st Shift or 2st Sh	jit Ti	me: 6750		,	•	
Unit	Visual Inspection NORMAL For ABNORMAL			Com	ments	
Visible Emission From Shaker	NOC	- The second sec	<u> </u>			
Visible Emission From Discharge Conveyor System	MAC	Malacontermination with a service			r.	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected ause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS	
Inspector: SmelKo	
Date of Inspection: Apr 29 14	
Shift: 1st Shift or 2st Shift Time: 5.00	
Unit Visual Inspection NORMAL FOR ABNORMAL	Comments
Visible Emission From Shaker NOR	
Visible Emission From Discharge Conveyor System NOR 7	E.

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected cause the greatest emissions.

• Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS Inspector: melko Date of Inspection: 4-30-14 Time: 500 Shift 2¹¹⁰ Shift Shift: Unit Visual Comments Inspection NORMAL ABNORMAL. Visible Emission From Shaker non

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected transformed during normal daylight operations and during the part of operations that would normally be expected transformed.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Visible Emission From Discharge Conveyor System

noR